
Desso Textile floor covering - Tiles

Fuse EcoBase™

Specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1	I/10 "					
Aspect	ISO 2424	Structured loop pile							
Dye method			Solution	dyed					
Dimension	EN 994	cm x cm	50 x 50 / 19,68" x 19,68" (20 tiles per box)						
Primary backing	ISO 2424		Polyester fleece						
Secondary backing	ISO 2424		Desso EcoBase® * - Containing at least 70% C2C positively defined recycled content						
Pile fibre composition	ISO 2424		BCF Polyamide 6 and ECONYL® (ECONYL® is made from 100% regenerated content) **						
Total thickness	ISO 1765	mm	6.5		inch	0.3			
Effective pile thickness	ISO 1766	mm	2.8		inch	0.11			
Total mass	ISO 8543	g/m²	4250		oz/yd²	125.4			
Total pile mass	ISO 2424	g/m²	730		oz/yd²	21.5			
Effective pile mass	ISO 8543	g/m²	415		oz/yd²	12.2			
Pile density	ISO 8543	g/cm³	0.148		lb/in³	0.0054			
Number of tufts	ISO 1763	/dm²	1580		/yd²	132104			
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10)9					
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		33 Commercial - heavy use						
Luxury rating	EN 1307		LC 2						
Dimensional stability	EN 986	%	≤ 0,2						
Impact sound reduction $\Delta L_{_W}$	ISO 10140	dB	23						
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000	
		α_s	0.01	0.03	0.06	0.15	0.26	0.31	
Noise reduction	ISO 354	$\alpha_{\rm w}$	0.15						
Thermal resistance	ISO 8302	m².K/W	0.063						
Flammability	EN 13501-1	EN 13501-1		Bfl - s1 (loose laid tested)					
Prodis - GUT	www.pro-dis.	www.pro-dis.info		5AFD3F4F					







- * DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle® Certified CM Product Standard Version 3.0. The total % of recycled content varies per product and per colour which can be found on our website: www.desso.com
- ** ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.desso.com.

Desso flooring products are to be installed in full accordance with Desso's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Desso flooring products should only be used as floorcoverings. Note: Desso reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit www. desso.com

